

PUMPERS



RESCUE-PUMPERS



TANKERS



RESCUES



WILDLANDS



- **Aluminum or Stainless steel formed body**
 - Aluminum — 3/16" 5052 sheet with aluminum sub-frame
 - Stainless — 12 gauge 304L with stainless sub-frame
- **Standard swirl finish aluminum pump house with stainless steel panels**
- **Full right side hinged access panel on pump house for superior maintenance and service access**
- **Full-finish interior on compartments with Zolatone® paint**
- **15 step PPG paint on body with durable, high luster finish**
- **VMUX solid state electronics for maximum programmable flexibility with strong system reliability**
- **Tank capacities up to 1000 gal in a UV stabilized polypropylene tank**
- **Industry first independent UL welder certification**
- **Body durability tested by American LaFrance at independent proving grounds**



BY AMERICAN LAFRANCE

LIBERTY™ PUMPER
CUSTOM AND COMMERCIAL

www.libertybyamericanlafrance.com

LIBERTY™ PUMPER

CUSTOM AND COMMERCIAL



Zolatone compartment finish



Aluminum pump house with stainless steel panels



Full access to pump house



Electrical node with access panel

These are the typical specifications for the Liberty™ Pumper by American LaFrance:

MODEL: Liberty Pumper by American LaFrance.

CHASSIS: Liberty custom chassis by American LaFrance, Freightliner M2, or Sterling Acterra.

CONSTRUCTION:
Aluminum: 5052-H32 3/16" formed body panels with integral 6063-T52 sub-frame.

Stainless: 304L 12-gauge formed body panels with integral stainless steel sub-frame.

MOUNT SYSTEM: American LaFrance proprietary Flexible Mount System (FMS).

BODY STYLES: Two body styles available with three full-height compartments on the left side and two low-height compartments on the right.

WATER CAPACITY: 750 or 1000 gal capacity polypropylene tanks.

PUMP HOUSE: Traditional aluminum pump house and overlap panel in side-mount and top-mount configurations.

PUMPS: Hale QFLO+ split-shaft 1250 GPM pump standard. Hale QMAX 1500 GPM pump optional.

FOAM SYSTEMS: Hale single or dual tank Class A or Class A/B direct injection system with integral foam cell optional.

DOORS: Roll-up doors standard. Hinged overlap doors optional.

LADDER STORAGE: Side wall storage brackets standard.

GENERATORS: 8 KW PTO-driven hydraulic generator (Liberty custom chassis), or compartment-mounted gasoline generators with capacities up to 5 KW (optional — either chassis).

LIGHTING: Body-mounted telescoping lights optional.



BY AMERICAN LAFRANCE

For your nearest American LaFrance dealer, call 1-888-253-8725.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. American LaFrance is ISO 9001 and 14001 certified. ©2005 American LaFrance, LLC. NOTE: American LaFrance is a registered ISO 9001 and 14001 manufacturer for Class 7 and Class 8 fire apparatus.